

Basic Description

Heat shrink joint for cables with XLPE insulation, Inline version

Electrical data

Relevant standard	IEC 60840 / IEEE 404	
Rated voltage $U_o/U (U_m)$	kV	36/66 (72.5)
Rated frequency	Hz	50/60
Lightning impulse voltage 1,2/50 μ s	kV	350
AC voltage withstand test (15 min)	kV	120
DC voltage withstand (15 min)	kV	245
Power frequency voltage withstand dry (1 min)	kV	175
Rated current	kA	as per cable
Rated short-circuit current (conductor)	kA	as per cable
Rated short-circuit current (sheath) 1s	kA	10


Mechanical data

Total length of joint (approx.)	mm	1350
Outer diameter of joint (approx.)	mm	up to 135

Design data

Diameter over insulation	30 – 86 mm (5 kit sizes)
Diameter over sheath	up to 100 mm
Cable screen types	Cu-wires w/o laminated foil, lead sheath, corrugated metal sheath, Cu-tape (other types and combinations on request)
Max. Cross section (Cu / Al)	approx. 1200 / 1200 mm ²
Conductor connection	mechanical (shear head bolts)
Material of connector	aluminium
Colour of outer protection	black
Material of outer protection	WCSM (Polyolefin)
Number of heat shrink tubes	4
Method of stress control	impedance
Box Size (L x W x H)	1620 x 260 x 240 mm
Weight joint kit (including connector) approx.	10.5 kg
Space required for assembly	2500 mm

© Tyco Electronics EPP-HVD-0040-10/09



While Tyco Electronics and its affiliates referenced herein have made every reasonable effort to ensure the accuracy of the information contained in this catalog, Tyco Electronics cannot assure that this information is error free. For this reason, Tyco Electronics does not make any representation or offer any guarantee that such information is accurate, correct, reliable or current. Tyco Electronics reserves the right to make any adjustments to the information at any time. Tyco Electronics expressly disclaims any implied warranty regarding the information contained herein, including, but not limited to, the implied warranties of merchantability or fitness for a particular purpose. Tyco Electronics' only obligations are those stated in Tyco Electronics' Standard Terms and Conditions of Sale. Tyco Electronics will in no case be liable for any incidental, indirect or consequential damages arising from or in connection with, including, but not limited to, the sale, resale, use or misuse of its products. Users should rely on their own judgment to evaluate the suitability of a product for a certain purpose and test each product for its intended application.

In case of any potential ambiguities or questions, please don't hesitate to contact us for clarification.